

Electric Solutions



PROFLO 125T1- Single Element



Specifications

Storage Capacity (L) Overall Height Overall Diameter Net Weight (Empty Kg) 130 (~34 Gallons)
1090
530
51



10 year tank warranty* 1 year full parts & labour warranty

No. of Adults & Children



Adult icon can represent dishwasher or washing machine. An adult icon does not represent a spa bath.

- 125L Proflo water heaters now boast a larger anode to increase tank life
- Hard-wearing, tough polymer base resists damage and moisture
- Features durable Y class commercial grade enamel
- Easy installation, water connections on both sides of tank
- Low maintenance and long service life
- Full flow pressure to all outlets
- Can be installed indoors or out
- Hard water option available
- Made in Australia
- 10 years tank warranty, 1 year parts and labour *

Heating Element	2.4 kW./ 240 V	3.6 kW./ 240 V	4.8 kW./ 240 V	6.0 kW./ 240 V
Service (per element)	10 Amps	15 Amps	20 Amps	25 Amps
Recovery (per element)	69 L/hr	103 L/hr/30°C rise.	138 L/hr/30°C rise.	172 L/hr/30°C rise.

* Warranty terms as specified by the vendor of each country.





Specification

The water heater shall be a DUX[®] model 125T1 suitable for mains pressure water supply. The storage cylinder shall be lined with Duro-namel [™] vitreous enamel suitable for operation up to 82°C. Internal anodic corrosion protection shall be provided. The water heater shall be completely insulated with high density polyurethane insulation and protected by a sealed Colorbond[®] metal case with access to the electrical element and thermostat. Electric immersion type, bolt mounted, heating element shall be fitted with an energy rating of ______Watts and controlled by an adjustable surface mounted thermostat complete with integral high temperature safety cut-out.

Local authority requirement

This product should be installed by a qualified plumber. Local Authority, Water Board and Building Regulations may apply to installation of this product, and you should consult the appropriate bodies on these requirements. Failure to comply may invalidate the product warranty.

*All Dux Proflo water heaters are dual-handed for ease of installation and operate at 240V AC single phase electricity supply. Specification and materials may change without notice.PROFLO & DUX are registered trademarks of Dux Manufacturing Limited.

